

Chiller with air-cooled refrigerating unit and circulation pump (stainless steel). Housing, atmospheric open tank and copper soldered evaporator made of stainless steel. With digital level indicator. Condenser in air-cooled design, performance-optimized by a built-in high-efficiency fan motor. Powerful feed pump with integrated overtemperature protection. The flow rate can be adjusted via the manual bypass valve on the backside of the chiller.

Control unit B400 / RB400:

Capacitive operating interface with OLED display and multi-coloured status notification for instant identification of the current operating status. Choice of eight different system languages (DE, EN, ES, FR, IT, PT, RU, TR). Separate operating option for the feed pump and the cooling unit with convenient adjustment of the desired setpoint. Operating of the system can be evaluated on a PC or notebook via an integrated RS232 interface.

Technical data according to DIN 12876

Operating temperature range	-20...+15 °C
Temperature stability at -10°C	±1.5 K
temperature set point / display	colour LED Touchscreen
Internal temperature sensor	Pt100
Interface digital	RS232
Safety classification	Class I / NFL
Cooling power	
at +15°C	3,5 kW
at +10°C	2,5 kW
at ±0°C	1,6 kW
at -10°C	0,98 kW
at -20°C	0,7 kW
Refrigeration machine	air-cooled, CFC- and HCFC-free
Refrigerant	R449A
Refrigerant quantity	2,0 kg
Gas warning sensor	without
Pressure pump	
max. delivery	50 l/min
max. delivery pressure	4.5 bar
Pump connection	G ½" male
Bath volume min.	24 l
Bath volume max.	37 l
sound pressure level +/- 4 dB(A)	60 dB(A)
Overall dimensions WxDxH **	580x660x820 mm
Net weight	121 kg
Power supply requirement	208V 2~ 60Hz
max. current	12,5 A
Fuse on power network side	2x 20 A
Degree of Protection	IP20
max. ambient temperature	+32 °C
min. ambient temperature	+5 °C



Order-No.: VDH1100664

from Serial-No.: **1479 19** **1.0/20**

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Accessories and periphery: 2pcs Hose nozzles \varnothing 13mm*, bath cover*, overpressure. Bypass valve, Bypass valve*, drain valve, thermofluid, RS232 cable

* standard accessories

Output data valid for: Room temperature 20°C. If the ambient temperature rises, the cooling capacity may drop.

In accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example: 5% voltage and +2% frequency -> not allowed! -

5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Recommended thermofluid: Water - Monoethylene Glycol 50:50

Standard delivery conditions - Power cable configuration:

1. Single-phase devices (115V) -> with cable and plug
2. Two-phase devices (208V) -> with cable, without plug
3. Three-phase devices (208V/460V) with current consumption less than 63A -> with cable, without plug
4. Three-phase devices (208V/460V) with current consumption greater than 63A -> with cable, without plug

** Please respect space requirements. See operating conditions at www.huber-online.com