



# CLS-3788-C13

## STANDARD DUAL TEMP REFRIGERATOR/FREEZER COMBO

The Standard Dual Temperature Combination Refrigerator/Freezer units are intended for general purpose applications only where precise temperature control and maintenance are not essential and there are no requirements for temperature alarms.

Select models have freezers which feature a manual defrost operating system to limit product-damaging temperature spikes found in auto defrost units. Periodic manual defrosting is required.

Models with auto defrost freezer compartments have programmed defrost cycles that will reach air temperatures of approximately 0°C.



Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL
CLS-3788-C13	20	Auto	2 Solid	1 Fixed Fr, 2 Adj/1 Fixed Ref	30	34 1/4	68 1/2	R134a

- Mechanical thermostat
- Adjustable operating temperature range:  
Refrigerator: 1°C – 10°C  
Freezer: -15°C – -25°C
- Magnetic door gasket for positive seal
- Heavy duty door handles
- Leveling legs
- Two probe access ports (3/8"); one, refrigerator/one, freezer

- White textured cabinet and door
- High density urethane foam cabinet and door insulation
- CFC-free (R134a) refrigerant, foam insulation and packaging
- Two year parts and labor warranty, plus an additional three year compressor parts warranty
- Defrost:  
Refrigerator: Cycle defrost  
Freezer: Auto & Manual defrost available

**DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assists in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.**