

# CLS-3788-R12

## PREMIER DUAL TEMP COMBO

Featuring separate microprocessor temperature controller allowing for precise temperature control, verification and recovery. An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings (REFRIGERATORS ONLY)

All models are equipped with digital temperature displays for convenient monitoring. Critical samples and supplies are security backed with an extensive package of audible and visual alarms. The freezer units feature an automatic defrost operating system.



Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL
CLS-3788-R12	10.5/1.3	Cycle/Auto	2 Solid	6 Adj. Ref/2 Adj Fr	23 3/4	26 1/2	80 1/4	R600a

- Microprocessor temperature controller, refrigerator and freezer
- Digital temperature display, refrigerator and freezer
- Adjustable operating temperature range:  
Refrigerator: 1°C – 10°C  
Freezer: -15°C – -25°C
- Audible and visual high and low temperature alarms, refrigerator and freezer
- Remote alarm contacts, refrigerator and freezer
- Forced draft circulation Refrigerator
- Keyed door locks
- Magnetic door gasket for positive seal
- Integrated door handles

- Leveling legs
- Two probe access ports (3/8"); one, refrigerator/one, freezer
- White powder coated exterior
- HFC-free refrigerant (R600a), foam insulation and packaging
- Two year parts and labor warranty, plus an additional three year compressor parts warranty
- Defrost:  
Refrigerator: Cycle defrost  
Freezer: Auto defrost
- UL/C-UL listed
- Please note these units require 2 outlets.

**DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assists in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.**