

CLS-3788-R23

STANDARD GLASS DOOR LABORATORY REFRIGERATOR

The all-new Standard Series Glass & Solid Door Laboratory Refrigerators are purpose built for scientific and medical applications. To improve performance over past solid door general purpose units, the new Standard Series Glass & Solid Door Laboratory Refrigerators feature a digital microprocessor temperature controller allowing for the precise temperature management necessary for critical samples and supplies. A forced air directional refrigeration system provides superior temperature uniformity and recovery after door openings. An automatic cycle-defrost design prevents product damaging temperature spikes.



Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL
CLS-3788-R23	23	Cycle	1 Swing Glass	4 Adj.	26 7/8	34 3/4	79 3/4	R134a

- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- Remote alarm contacts
- Adjustable operating temperature: 1°C to 10°C
- Magnetic door gasket for positive seal
- Heavy duty door handle
- Casters with footed brake

- LED interior lights are safety shielded and switch controlled
- Probe access port (3/8")
- Powder coated steel white interior and exterior
- High density urethane foam cabinet insulation
- CFC-free refrigerant (R134a), foam insulation and packaging
- One year parts and labor warranty, plus an additional four year compressor parts warranty
- UL/C-UL listed