

CLS-3788-R50



STANDARD GLASS DOOR CHROMATOGRAPHY REFRIGERATOR

The Standard Chromatography Refrigerators feature a microprocessor temperature controller and display, allowing for precise temperature control, verification and recovery versus mechanical style thermostats. One interior duplex electrical outlet and one side wall port hole is provided to simplify the setup and operation of laboratory procedures. An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings.

All Chromatography Plus units require two electrical outlets.



Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL
CLS-3788-R50	49	Cycle	2 Swing Glass	8 Adj.	54 3/4	34 3/4	79 3/4	R134a

- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- Remote alarm contacts
- Adjustable operating temperature: 1°C to 10°C
- Magnetic door gasket for positive seal
- Heavy duty door handle
- Casters with footed brake
- LED interior lights are safety shielded and switch controlled

- One GFCI protected duplex electrical outlet
- One 2" access port with spring loaded self-closing, gasketed metal cover
- Probe access port (3/8")
- Powder coated steel white interior and exterior
- High density urethane foam cabinet insulation
- CFC-free refrigerant (R134a), foam insulation and packaging
- One year parts and labor warranty, plus an additional four year compressor parts warranty
- UL/C-UL listed